



Quote  
#12446  
1/17/2025

**Bill To**  
Jason Dietsch Sales  
227 East Morrison  
Edgerton OH 43517  
United States

Expires	Sales Rep	Shipping Method
2/16/2025	Brian Hixenbaugh	DPU

Qty	Description
1	2025 USH-8.532TR70

#### Standard Features

##### Hitch

1 EA	7-Way Molded Plug	24780
1 EA	Breakaway kit w/charger	24160
2 EA	Safety Chain	1710

##### Frame

1 EA	Frame - Rear Wing Option	65150
1 EA	I- Beam - 8" inch I Beam Frame - double beam	62880

##### Interior

1 EA	United Logo Stepwell, .080 smooth alum, int. rear corner covers, last 6in.of floor	66670
1 PTL	Box off sidewalls to reduce dust	35020

##### Exterior

1 PTL	4in. Bottom Molding	31390
1 PTL	Conspicuity Tape	30420
1 EA	ATP Stoneguard	33020
1 PAIR	Bright Aluminum - Front Corners	18240
1 EA	Bright Aluminum - Front Wrap	32360
1 EA	End Cap - front corners and rear corners	57100
1 EA	License plate bracket raise 12"	55290
1 EA	Rear Wing- Option	59220
1 EA	Recessed Top Aluminum Extrusion	32590
1 LF	Roof - One Piece Aluminum	18420
1 EA	Taped Exterior Metal	64030

##### Door

0 EA	Door Hold Back Aluminum Heavy Duty	59440
1 EA	License plate bracket holder raise 12"	55300
1 EA	Steel Step well	62540

##### \*Notes

1 EA	3 year limited warranty	64620
------	-------------------------	-------

##### Height

32 Each	25 - 36" height
	25 - 36" height

1 Each **Final Height 9ft 6in**  
Interior Height is 9ft. 6in.

#### Axle

1 Each **Triple Spread Axles : 5" spread between axles**  
Triple Spread Axles : 5" spread between axles  
Spread Axle NOTE  
NOTE: if 6" I beam & 5 or 6 bolt axles raise wheel well 2in. unless there is a jump door raise gusset to top of wheel box instead.incl drop axles

3 Each **Axle Quantity - Triple Axle**  
Axle Quantity - Triple Axle

1 Each **7000# Electric Brake Axle #13 A- Standard**  
7000# Electric Brake Axle #13 A- Standard

#### Cabinets

10 Foot **Aluminum Base Cabinet**  
Aluminum Base Cabinet, Location: (1) 6FT base cabinet R/S start at front of trailer and go rearward, (1) 4FT base cabinet CS start at front of trailer and go rearward, NOTE:  
the 4FT base cabinet is for engine storage, no stiles, single cabinet door

1 Each **Color of Cabinet: White Cabinet**  
Color of Cabinet: White Cabinet

1 Foot **Aluminum Overhead Cabinet -16"H X 16"D**  
Aluminum Overhead Cabinet -16"H X 16"D  
Location: Use for integrated 110V/12V electrical panel, mount on front wall close to C/S wall, top of cabinet should be just under platform SEE PRINT

#### Options

1 Each **TRAILER IS GOING TO OPTIONS DEPARTMENT**  
TRAILER IS GOING TO OPTIONS DEPARTMENT  
THIS TRAILER HAS ITEMS THAT REQUIRE IT TO GO TO THE OPTIONS DEPARTMENT

1 Each **Air Line - Inlet W/ 3 Couplings**  
Air Line - Inlet W/ 3 Couplings location: (1) Interior R/S rear of trailer 6FT AFF, (1) above R/S base cabinet 42 AFF located 1 FT from front of trailer and go rearward, (1) above platform 12IN AFF platform R/S wall 1FT from front of trailer and go back-SEE PRINT

#### Electrical

1 Each **Air Compressor Wiring Kit**  
Air Compressor Wiring Kit -Includes switch, recept, breaker and wiring  
  
(1) Switch - wall 110v to 20amp Location: C/S wall 42IN AFF 1FT toward rear from front of trailer-SEE PRINT  
(1) Recept 110v interior Duplex 20amp Location: C/S wall of trailer 18IN AFF platform near front wall-SEE PRINT

5 Each **Recept - 110V Interior Duplex**  
Recept - 110V Interior Duplex LOCATIONS: (1) each R/S and C/S at rear of trailer 18IN AFF;  
(1) C/S wall above C/S base cabinet 1FT from front of trailer and go rearward 42IN AFF,  
(2) R/S wall above R/S base cabinet 42IN AFF, 1 of them 3FT and one of them 5FT from front and go back - SEE PRINT

1 Each **A/C -15,000 BTU w/ Heat strip and remote thermostat**  
A/C -15,000 BTU w/ Heat strip and remote thermostat  
Location: 16FT from front of trailer and go rearward

1 Each **Motorbase Plug - 50Amp**  
Motorbase Plug - 50Amp LOCATION: Low and recessed by C/S tongue tube-SEE PRINT

- 1 Each **Panel Box - 50 Amp Panel Box w/ Converter All-in-One (Cabinet Required)**  
50 amp panel box with converter all in one  
Panel box and converter#(PD4560K18-L-18DC LED30A/50A AC) w/12 volt disconnect knob#701B between battery, converter, life line, cable hatch. Location: In 1FT 16INx16IN overhead cabinet on front wall of trailer by C/S wall, top of cabinet should be at bottom of car platform-SEE PRINT

(1)Note: Panel box is 110v / 12v box and converter

- 1 Each **Recept - 110V GFI Exterior**  
Recept - 110V GFI Exterior  
LOCATION: C/S low and recessed just to rear of wheel box-SEE PRINT

#### Tires

- 6 Each **ST235/80 R 16 G Sterling on Black and Silver Eagle Alum Wheel**  
ST235/80 R 16 G Sterling on Black and Silver Eagle Alum Wheel

#### Tire Accesories

- 1 Each **Spare Tire - ST235/80 R 16 G Sterling on Black and Silver Eagle Alum Wheel**  
Spare Tire: ST235/80 R 16 G Sterling on Black and Silver Eagle Alum Wheel - Ship Loose

#### Frame

- 2 Each **Battery Box - Recessed (16in. X 10in. X 12in. deep)**  
Battery Box - Recessed (16in. X 10in. X 12in. deep)  
Location: Under R/S base cabinet toward rear of cabinet-SEE PRINT
- 6 Foot **Platform-Car Deck/Storage**  
Platform-Car Deck/Storage: LOCATION: Start at front of trailer and extend platform rearward 6FT, bottom of platform is 6FT 10IN AFF SEE PRINT
- 1 Each **Rear Wing Option**  
Rear Wing Option w/ powder coated gussets - BLACK  
Do not walk on rear wing even if walk on roof option is on trailer.
- 1 Each **Beavertail, Ramp Door, Spring & Flap - 6' Beavertail - Frame**  
Beavertail, Ramp Door, Spring & Flap - 6' Beavertail
- 1 Pair **4" Corner Posts (With Price)**  
4" Corner Posts
- 32 Foot **Upgrade Wall Posts-Nascar Upright -16" O.C.**  
Upgrade Wall Posts-Nascar Upright -16" O.C.
- 1 Pair **Skid Roller - Mount on Rear**  
Skid Roller - Mount on Rear  
Weld to frame
- 1 Each **Winch Plate**  
Winch Plate  
Location: against C/S wall just ahead of wheel box (start 18FT from rear of trailer and go forward)-SEE PRINT
- 1 Each **Crossmembers - 16in o.c.**  
Crossmembers - 16in o.c.
- 1 Each **Spare Tire Well(Recessed)**  
Spare Tire Well (Recessed) LOCATION: Centered start 9FT back from front of trailer and go rearward, hinges on rear side of compartment for lid-SEE PRINT
- 32 Foot **Upgrade 16" on Center to 12" on Center Roof Bows**  
Upgrade 16" on Center to 12" on Center Roof Bows

- 2 Each **Backer Plate**  
Backer Plate -(2) steel backer plates for future tire rack  
LOCATION: Start 4FT from R/S rear of trailer and go forward 8FT, (1) 76IN AFF and (1) 100IN AFF  
SEE PRINT

#### Hitch

- 1 Each **Coupler -25000# Bolt on Standard**  
Coupler -25000# Bolt on Standard
- 1 Each **ATP Hitch Cover**  
ATP Hitch Cover
- 1 Each **1' Extended Tongue w/ 3rd Member (11 gauge)**  
Extended Tongue w/ 3rd Member (11 gauge)  
Trailer Must Have Double I-Beam -Upgrade if Necessary  
-Delete std coupler that comes in Model\*  
-Delete std jack and foot pad that comes with model.  
-Delete std tongue
- INCLUDED:  
(1) Coupler - 2 5/16 Bolt on (20,000#)  
(1) Jack - 7000# Square drop leg w/pin - Removable
- 1 Each **Jack - 7000# Square Drop Leg with Pin - Removable (No Price)**  
Jack - 7000# Square Drop Leg with Pin - Removable
- 1 Each **Tongue 3rd Member**  
Tongue Third Member (UXT & USH)

#### Interior

- 40 Foot **Floor Covering-Raised Small Coin Black**  
Floor Covering-Raised Small Coin Black  
LOCATION: Ramp door and floor of trailer
- 32 Foot **Ceiling-3/8" Plywood**  
Ceiling-3/8" Plywood
- 36 Foot **E-Track -Recessed - trim out with smooth aluminum mill finish**  
E-Track -Recessed - trim out with smooth aluminum mill finish  
This E track is welded in and rated at 2300# / trim with smooth aluminum mill finish - Locations: Starting 6IN from rear of trailer and going forward: Install (2) 2FT sections centered 60IN apart, then go forward 8FT and install (2) 8FT sections centered 60IN apart, then go forward 5FT and install (2) 8FT sections centered 35IN apart-SEE PRINT
- 32 Each **Wall - Carpeting (marine grade) on wall 36" tall - Black**  
Wall - Carpeting (marine grade) on wall 36" tall  
Color: Black  
LOCATION: from rear of trailer then 28FT forward C/S wall, 26FT forward R/S wall and 6FT forward above platform R/S and C/S from rear of platform to front wall of trailer
- 1 Each **J Rail for Cove Trim**  
J Rail for Cove Trim
- 32 Foot **Insulated White Aluminum Ceiling**  
Insulated White Aluminum Ceiling - Add Luan Backer
- 32 Foot **Floor - 3/4in Plywood Floor**  
Floor - 3/4in Plywood Floor
- 1 Each **STD. Wall - White Aluminum interior walls over 3/8in plywood wall liner**  
STD. Wall - Screwless White Aluminum interior walls over 3/8in plywood wall liner

- 15 Foot **Tie Downs - E-Track - Surface Mounted**  
Tie Downs - E-Track - Surface Mounted, LOCATIONS: (2) 6FT sections R/S wall start 6FT from front and go rearward { (1) 12IN AFF and (1) 28IN AFF }; (1) 3FT section R/S start 4FT from front and go rearward 24IN AFF - SEE PRINT
- 1 Each **Tie Downs - Heavy Duty D-Rings (Bolt-In)**  
Tie Downs - Heavy Duty D-Rings (Bolt-In)  
  
These D-rings are bolted in and rated at 5000# use carriage bolts - Heavy duty, Location: Centered, 19FT from rear of trailer-SEE PRINT

#### Exterior

- 32 Each **.050 Black**  
.050 Black
- 1 Pack of 2 **Cast Corners - Polished (USH)**  
Cast Corners - Polished (USH)
- 1 Each **Roof - Lauan down center of roof only**  
Roof - Lauan down center of roof only  
Lauan down center of roof ONLY 48" wide
- 1 Each **Exterior Trim Mill**  
Exterior Trim Mill
- 6 Each **Flare - 23in Single Wheel Flares**  
Std. Flare - 23in Single Wheel Flares
- 32 Foot **4in. Bottom Molding**  
4in. Bottom Molding

#### 12 Volt Electrical

- 1 Each **Diode for 14" Angled Scene Light**  
Diode for 14" Angled Scene Light
- 6 Each **Exterior Light - 14" Angled Scene Light - (Nova)**  
Exterior Light - 14" Angled Scene Light - (Nova)  
Surface mounted angled Scene light: Location: (3) at rear of trailer under wing evenly spaced, (3) C/S exterior 9FT AFF evenly spaced, SEE PRINT  
  
INCLUDES:  
(1) Backer required each for 14inch scene light
- 10 Each **Exterior Light - LED Recessed Clearance Lights (Extra)**  
Exterior Light - LED Recessed Clearance Lights (Extra)  
LOCATION: (5) additional RS and CS, two rows evenly spaced(hi and lo), put lower row in line with midship turn signal-SEE PRINT
- 8 Each **Interior Light - 14" LED Hux Utility Light - Trailer must have a ceiling liner if installed on ceiling**  
Interior Light - 14" LED Hux Utility Light - Trailer must have a ceiling liner if installed on ceiling  
LOCATIONS: (1) centered on ceiling above platform start at from wall and go rearward 3FT  
(3) Under platform, 1 pair 3FT from front wall and go rearward 48IN apart, (1) centered under platform 5FT from front and go rearward  
(4) Centered on ceiling, evenly spaced between rear of platform and rear of trailer-SEE PRINT
- 1 Each **Stub Wire - 12V**  
Stub Wire - 12V: LOCATION C/S near winch plate just ahead of C/S wheel box, use heavy gauge wire for future winch installation-SEE PRINT
- 2 Each **Switch - 110V Style Single (For 12V Component)**  
Switch - 110V Style Single (For 12V Component) LOCATIONS: (1) C/S rear of trailer for C/S Exterior NOVA scene lights LOCATION: (1) R/S rear of trailer for Exterior NOVA scene lights under rear wing-SEE PRINT
- 1 Pack of 2 **Exterior Light - LED Back Up (Docking) Light**  
Exterior Light - LED Back Up (Docking) Light

- 1 Pack of 2     **Exterior Light - LED Mid Ship Turn Signal (Amber)**  
Exterior Light - LED Mid Ship Turn Signal (Amber)
- 1 Each        **Exterior Light - Surface-Mounted Porch Light**  
Exterior Light - Surface-Mounted Porch Light, Location: Centered above entry door on front wall of trailer-  
SEE PRINT
- 1 Each        **Std. Switch - 12V Single Wall**  
Std. Switch - 12V Single Wall, Location: Front wall of trailer just to the C/S of entry door 48IN AFF-use for  
exterior LED porch light -SEE PRINT
- 1 Each        **Tail lights angle mounted on ramp door**  
Tail lights angle mounted on ramp door
- 1 Each        **LED Clearance & Tail Lights For Entire Unit**  
LED Clearance & Tail Lights For Entire Unit
- 3 Pack of 2    **STD Exterior Light - LED Surface Mount Tail W/ Chrome Ring**  
STD Exterior Light - LED Surface Mount Tail W/ Chrome Ring
- 1 Each        **Switch - 110v in place of 12v 3 way switch**  
Switch - 110v in place of 12v 3 way switch, Location: (1) C/S at rear of trailer, (1) on front wall of trailer just  
to the C/S of entry door SEE PRINT
- 1 Each        **Battery - 12V Deep Cycle w/ Box**  
Battery - 12V Deep Cycle w/ Box  
Location: (1)In recessed battery box under R/S base cabinet, NOTE: Customer will provide his own battery  
for second recessed battery box-SEE PRINT

#### Door

- 
- 1 Each        **Steel Rear Ramp Door - 4000lb. Reinforcement**  
Steel Rear Ramp Door - 4000lb. Reinforcement
  - 1 Each        **Rear Ramp Door - Heavier Ramp Door Double Spring**  
Rear Ramp Door - Heavier Ramp Door Double Spring  
Double spring,
  - 8 Foot        **Ramp Door Single 3/4" Plywood**  
Ramp Door Single 3/4" Plywood
  - 1 Each        **Ramp Flap - 16in. Aluminum**  
Ramp Flap - 16in. Aluminum  
IPO PLYWOOD FLAP
  - 1 Each        **Ramp door with 6' Beavertail - Door**  
Ramp door with 6' Beavertail w/ Flap, raise ramp door with extra height (8FT door length)
  - 2 Each        **Std. Alum - Grab handle For Ramp Door**  
Std. Alum - Grab handle For Ramp Door
  - 1 Pack of 2    **STD. Recessed Camlocks (Rear door)**  
STD. Recessed Camlocks (Rear door)
  - 1 Each        **RV Door - 32 x 78 Blank - IPO Standard Side Door**  
RV Door - 32 x 78 Blank - IPO Standard Side Door  
LOCATION: Centered on front wall of trailer, right hand hinged SEE PRINT
  - 1 Each        **Step - Steel Pull Out**  
Step - Steel Pull Out LOCATION: Welded to C/S tongue tube of hitch approximately 2FT forward of front  
wall of trailer-SEE PRINT
-